



VENKATARAMANA Graphics Pvt. Ltd.

Building Trust Through Service

Eyecolor®

JC-3350G

Ultra-wide custom flatbed printer

(Magnetic suspension linear motor is optional)



JC-3350G	Technical Parameter	
Print Head	G5X3	G6X3
Print Head	3-8pcs	
Color	CMYK+LcLm+White+Varnish	
Print height	2-90mm	
Max print Size	3300mm*5000mm	
Print Resolution	720*600, 720*900, 720*1200dpi	
(1W+2C) 3	4PASS: 18m ² /h	4PASS: 24m ² /h
Print Speed (for 3 heads)	6PASS: 12m ² /h	6PASS: 16m ² /h
	8PASS: 9m ² /h	8PASS: 12m ² /h
RIP Software	Photoprint/PrintFactory	
File Format	TIFF, JPEG, PostScript, EPS, PDF	
Ink Type	Soft / HARD UV ink	
Machine Size	6060*5180*1380mm(L*W*H)	
Packing Size	6060*3400*1200mm(L*W*H)	
Weight	NW:2100KG, GW:2400KG	
Environment Request	Temperature 18-28°C, Humidity40%-60%	
Input Voltage	50Hz/60Hz, 220V (±10%) >35A	



Multiple printing modes



Anti-static nozzle



Automatic nozzle height measurement



Smart RIP

Printable Media:

Glass, aluminum-plastic panels, wood panels, aluminum gussets, organic panels, ceramics, metal panels, jade, etc.,

Technical Parameters:



Ricoh Gen5 Print Head




400W FUJI Servo



1.5KW Vacuum fan



Water-cooled LED lamp system



anti-static electricity ,
anti-collision device



High Resoution Negative
Pressure System

VENKATARAMANA Graphics Pvt. Ltd.

6-2-969, Flat No - 504,
Intech Residency,
Opp. Sant Nirankari Bhawan,
Khairatabad, Hyderabad-500004,
+91 94406 74130, +91 90300 21567
e-mail: info@svgpl.com

Nagpur,
Nitin Halder,
+91 8125 222 957
e-mail: info@svgpl.com

Delhi,
C-444, Vikasपुरi, New Delhi.
+91 94406 74130
e-mail: info@svgpl.com

www.svgpl.com