



VENKATARAMANA Graphics Pvt. Ltd.

Building Trust Through Service



VENKATARAMANA Graphics Pvt. Ltd.

Building Trust Through Service

AUTOLOADER MAT800 SERIES



The information in this manual is for reference only. Actual products may differ. Amsky reserves the right to change it without prior notice and the right for the final explanation.

VENKATARAMANA Graphics Pvt. Ltd.

6-2-969, Flat No - 504,
Intech Residency,
Opp. Sant Nirankari Bhawan,
Khairatabad, Hyderabad-500004,
+91 94406 74130, +91 90300 21567
e-mail: info@svgpl.com

Nagpur,
Nitin Halder,
+91 8125 222 957
e-mail: info@svgpl.com

Delhi,
C-444, Vikaspuri, New Delhi.
+91 94406 74130
e-mail: info@svgpl.com

www.svgpl.com

AUTOLOADER MAT800 SERIES



Autoloader MAT800 Technical Specifications

| | |
|------------------------|---|
| Model | MAT800 |
| Cassette Type | Multi-cassette (4 cassettes) |
| Plate Feeding Way | Auto-feed (Remove the interleaving paper at the same time) |
| Plate Speed | 76 plates/hour |
| Plate Size | Max. 1130mm x 920mm Min. 510mm x 400mm |
| Plate Thickness | 0.15mm - 0.3mm |
| Plate Loading Quantity | 400 plates (4x100 plates/cassette) |
| Plate Stacking | Manual stacking plates in cassette |
| Interface | Rs485 |
| Net Weight | 560 KG's |
| Device Size | 1,683 x 1,460 x 1,280mm (W x D x H) The height of MAT800 plate exit above ground level is about 1020mm |
| Air Supply | ≥0.65 MPa |
| Power Supply | Single Phase: 200 - 240V; Max Power (Peak Value): 1100W |
| Environment | Recommended temperature: 21-25° C Allowable Temperature: 15-30° C Relative humidity: <70% |