

GO BIG ON POSSIBILITIES AND PRECISION.



Distinctive Quality Meets Endless Possibilities For Your Creative Ideas.

Take your ideas to a bigger scale with greater performance and precision with the Epson SureColor T-series printers. With PrecisionCore printhead technology and UltraChrome XD2 ink^{®2} to bring about fast printing speeds, enjoy a seamless work process and top-class accuracy in every print. Showcase your ideas and plans in a big way right down to the finest detail.

GO BIG on the details and find out more from our printing experts.



IT'S IN THE DETAILS.



- Detailed Accuracy**
PrecisionCore printhead technology produces impressive accuracy and sharpness at outstanding speeds.
- Reliable Efficiency**
In-built functions such as Continuous Ink Supply System^{®3} and seamless scan to print ensure high productivity.
- Small Footprint**
Minimally designed to fit effortlessly into tight working spaces.

*1 SC-T3130X stand is optional and is not included in the initial packaging. *2 For SC-T3130/T3130M/T5130/T5130M only. *3 For SC-T3130X only.

Dimensions and Weight	
SC-T3130M Weight: 33.4kg	
SC-T5130M Weight: 54.8kg	

SC-T3130M Weight: 33.4kg	
SC-T5130M Weight: 54.8kg	

SPECIFICATIONS		
MODEL NUMBER	SC-T3130M	SC-T5130M
Printer Width	24"	36"
Printing Technology	PrecisionCore TFP Printhead	
Print Head	3,200 nozzles (800 nozzles x 4 channels x 1 head)	
Nozzle Configuration	2,400 x 1,200 dpi	
Maximum Resolution	4.0 pl	3.7 pl
Minimum Ink Droplet Volume	±0.1% or ±0.26 mm	
Line Accuracy	0.07mm ¹ (0.02mm ²)	
Minimum Line Width	CAD (A1): 34 seconds	
Print Speed	CAD (A1): 31 seconds	
Ink System	UltraChrome XD2 Pigment Ink	
Ink Type	Cyan, Magenta, Yellow, Black	
Colours	Cyan, Magenta, Yellow, Black	
Paper Handling	2" core, Max 110 mm/3kg	
Maximum Roll Diameter / Weight	2" core, Max 119 mm/5.9kg	2" core, Max 119 mm/5.9kg
Roll: 329 mm - 610 mm	Roll: 297 mm - 914 mm	Roll: 297 mm - 914 mm
Cutsheet: 210 mm - 610 mm	Cutsheet: 210 mm - 914 mm	Cutsheet: 210 mm - 914 mm
Side Margin	3mm	
Media Thickness	Roll: 0.05 mm to 0.21 mm, ASF/Cutsheet: 0.12 mm to 0.27 mm	
Auto-Sheet Feeder	A4 to A3	
Paper Capacity for ASF	50 sheets plain paper / 5 sheets special media	
Scanning	CIS	
Sensor	RGB LED	
Light Source	600 dpi	
Optical Resolution	1.5 ips (Colour) / 4.5 ips (Mono)	
Scan Speed (200 dpi)	148 mm x 148 mm	
Minimum Document Size	609.6 mm x 2,720 mm	
Maximum Document Size	914.4 mm x 2,720 mm	
Scan Formats	JPEG, PDF (Single Page), PDF (Multi Page), PDF/A (Single/Multi), TIFF	
Scan to Destination	Scan to Network Folder, Scan to FTP Server, Scan to Email, Scan to Memory Device	
Copy	77 sec (Colour) / 60 sec (Mono)	
Copy Speed	25 to 400%	
Scaling	99	
Maximum Copies	USB 3.0, Ethernet (100BASE-TX/1000BASE-T), Wi-Fi (IEEE802.11b/g/n)	
Connectivity	Wi-Fi Direct (Simple AP)	
Interface	4.3" Touch Screen	
Wi-Fi Direct	ESC/P raster, HP-GL/2HP RTL	
Control Panel	1GB + 8GB ³	
Printer Languages	PDF ⁴ , TIFF, JPEG	
Printer Languages	Windows XP SP3 or later / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019, Mac OS X 10.6.8 or later	
Memory	Windows XP SP3 or later / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019, Mac OS X 10.6.8 or later	
Operating System Requirements	Mac OS X 10.6.8 or later	

SC-T3130M Weight: 33.4kg	
SC-T5130M Weight: 54.8kg	

SC-T3130X Weight: 29kg	
SC-T5130 Weight: 46kg	

Electrical Specifications	
Rated Voltage / Frequency / Current	AC 100 to 240V, 50/60Hz, 1.4A
Power Consumptions	Operating: Approx. 24W Ready: Approx. 11W Sleep: Approx. 2.0W Power Off (Stand by): Approx. 0.2W
Environmental Conditions	Operating: 10°C to 35°C, Storage: -20°C to 40°C
Temperature	Operating: 20 - 80% (No Condensation), Storage: 5 - 85% (No Condensation)
Humidity	Operating: Approx. 47dB(A) Operating: Approx. 50dB(A)
Sound Pressure	Operating: Approx. 6.6dB(A)
Sound Power	
Printer Dimensions	
Dimension With Stand (W x H x D)	970 x 974 x 696 mm 1,268 x 975 x 696 mm
Dimension Without Stand (W x H x D)	970 x 292 x 505 mm N/A
Weight With Stand	44.4 kg 54.8 kg
Weight Without Stand	33.4 kg N/A
What's In The Box	Printer, Printer Stand ⁵ , Initial Ink Cartridge, AC Power Cable, Setup Guide, Software CD-Rom, Maintenance Box
Warranty	1-year Warranty

*1 ISO/IEC 24790. Single weight matte paper, CAD/Line Drawing, Max Quality, High Speed-Off, Finest Detail-On.
*2 Addressable.
*3 For scanner data processing
*4 PDF available only for files scanned by integrated scanner.
*5 No stand included for SC-T3130M model.
EPSON INDIA PVT. LTD.
11th Floor, Godrej Centre - Habbal, Sy. No. 26,
Bellary Road, Sahakar Nagar, Byatarayanapura,
Bangalore - 560 092 Karnataka
Tel: 080 6939 5000 Fax: 080 6939 50055005



CONTACT EPSON TODAY! EMAIL: pravin@eid.epson.co.in




Epson Helpline: For product info or service - 1800 425 0011
For service: 1800 123 001 600 or 1860 3000 1600 (9 am - 6 pm) (Mon - Sat)
Email: ifp@epson-india.in www.epson.co.in

SPECIFICATIONS			
MODEL NUMBER	SC-T3130 / SC-T3130N	SC-T3130X	SC-T5130
Printer Width	24"		36"
Printing Technology	PrecisionCore TFP Printhead		
Print Head	3,200 nozzles (800 nozzles x 4 channels x 1 head)		
Nozzle Configuration	2,400 x 1,200 dpi		
Maximum Resolution	4.0 pl	3.5 pl	4.0 pl
Minimum Ink Droplet Volume	±0.1% or ±0.26 mm		
Line Accuracy	CAD (A1): 34 seconds		
Print Speed	CAD (A1): 31 seconds		
Ink System	UltraChrome XD2 Pigment Ink		
Ink Type	Black: Pigment, Colour: Dye		
Colours	Cyan, Magenta, Yellow, Black		
Paper Handling	2" core, Max 110 mm/3kg		
Maximum Roll Diameter / Weight	2" core, Max 119 mm/4.2kg	2" core, Max 119 mm/5kg	2" core, Max 119 mm/5kg
Roll: 329 mm - 610 mm	Roll: 297 mm - 610 mm	Roll: 329 mm - 914 mm	Roll: 329 mm - 914 mm
Cutsheet: 210 mm - 610 mm	Cutsheet: 210 mm - 610 mm	Cutsheet: 210 mm - 914 mm	Cutsheet: 210 mm - 914 mm
Side Margin	3mm		
Media Thickness	Roll: 0.05 mm to 0.21 mm, ASF/Cutsheet: 0.12 mm to 0.27 mm		
Auto-Sheet Feeder	A4 to A3		
Paper Capacity for ASF	50 sheets plain paper / 5 sheets special media		
Connectivity	USB 3.0, Ethernet (100BASE-TX/1000BASE-T), Wi-Fi (IEEE802.11b/g/n)		
Interface	Wi-Fi Direct (Simple AP)		
Wi-Fi Direct	4.3" Touch Screen		
Control Panel	ESC/P raster, HP-GL/2HP RTL		
Printer Languages	1GB + 8GB ³		
Printer Languages	PDF ⁴ , TIFF, JPEG		
Scanner Integration	Windows XP SP3 or later / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019, Mac OS X 10.6.8 or later		
Memory	Windows XP SP3 or later / Vista / 7 / 8 / 8.1 / 10, Windows Server 2003 / 2008 / 2012 / 2016 / 2019, Mac OS X 10.6.8 or later		
Operating System Requirements	Mac OS X 10.6.8 or later		
Electrical Specifications	AC 100 to 240V, 50/60Hz, 1.4A		
Rated Voltage / Frequency / Current	Operating: Approx. 28W Ready: Approx. 8W Sleep: Approx. 1.6W Power Off (Stand by): Approx. 0.2W		
Power Consumptions	Operating: Approx. 22W Ready: Approx. 8W Sleep: Approx. 1.6W Power Off (Stand by): Approx. 0.2W	Operating: Approx. 28W Ready: Approx. 8W Sleep: Approx. 1.6W Power Off (Stand by): Approx. 0.2W	Operating: Approx. 28W Ready: Approx. 8W Sleep: Approx. 1.6W Power Off (Stand by): Approx. 0.2W
Environmental Conditions	Operating: 10°C to 35°C, Storage: -20°C to 40°C		
Temperature	Operating: 20 - 80% (No Condensation), Storage: 5 - 85% (No Condensation)		
Humidity	Operating: Approx. 49dB(A), Sleep: Approx. 32dB(A)		
Sound Pressure	Operating: Approx. 7.5dB(A)		
Sound Power			
Printer Dimensions			
Dimension With Stand (W x H x D)	970 x 913 x 696 mm	970 x 928 x 577 mm	1,268 x 913 x 696 mm
Dimension Without Stand (W x H x D)	970 x 230 x 505 mm	970 x 245 x 577 mm	1,268 x 230 x 505 mm
Weight With Stand	38 kg	40 kg	46 kg
Weight Without Stand	27 kg	29 kg	33 kg
What's In The Box	Printer, Printer Stand ¹ , Initial Ink Cartridge, AC Power Cable, Setup Guide, Software CD-Rom, Maintenance Box		
Warranty	3-years Warranty	1-year Warranty	3-years Warranty

*1 No stand included for SC-T3130N model.

© 2023 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.



Information correct at time of printing
Printed December 2023

